



Fountainettes

Silver King's new modular fountainette helps you cash in on high profit dessert options. Flexible design allows you to use the SKF2A alone, or with a dry storage cabinet attached to either side!



assembled view



Dry Storage Cabinet



model SKF2A

Silver King SKF2A Specifications

- EXTERIOR** *Stainless steel*, galvanized back. Stainless steel back optional.
- INTERIOR** Corrosion-resistant material with coved corners throughout for fast, easy cleaning and sanitation.
- INSULATION** *Environmentally friendly* foamed-in-place polyurethane insulation for maximum insulation, strength and durability.
- DOOR** Polyurethane insulation, extruded aluminum frame, stainless steel exterior door panel, and extra heavy duty magnetic "*Thermo Rubber*" door gasket combine to make the toughest, longest lasting door in the industry. Easily field reversible.
- SHELVES** Heavy gauge wire shelves are *hand dipped*, not sprayed, providing double thick epoxy coating for superior durability and smooth finish. Adjustable in ½ increments on stainless steel pilasters. Dry storage cabinet shelf is stainless steel and adjustable in ½ increments.
- LEGS** Model SKF2A and Dry Storage Cabinet have flush-to-floor bases. Optional caster mobility kit available.
- PREPARATION SURFACE** Five syrup jars and four pumps, including one heavy-duty chocolate syrup pump. Five topping pans - two ¾ size (6" deep) with covers and ladles, and three ½ size (4" deep) with covers. Dry storage (P/N 10345-01) features 20 ¾" deep X 21" wide work surface plus a back splash with appliance receptacle cut-out.
- REFRIGERATION** CFC-free, 134a refrigerant, hermetically sealed, *high efficiency*, self contained refrigeration system features automatic defrost and forced air circulation. Adjustable temperature control and built in temperature indicator standard. Automatic condensate evaporator means no plumbing or floor drains.
- ASSEMBLY** Dry Storage Cabinet easily attaches to either side of SKF2A with eight screws. Holes are pre-drilled and tapped.
- ELECTRICAL** Standard as 115 volt, 60 Hz, single phase operation with 8 foot, 3 wire power cord with NEMA 5-15P plug.
- LISTINGS** Underwriters Laboratories, Inc. (U.S. and Canada), NSF International.
- WARRANTY** One year warranty on cabinet and refrigeration system against defective material or faulty workmanship. 90 days labor. Five year warranty on compressor. Full warranty information available upon request.

MODEL	EXTERIOR DIMENSIONS		STORAGE CAPACITY	SHELF AREA	NUMBER SHELVES	COMPRESSOR	AMPS	APPRX. SHPG WT.
	LENGTH	DEPTH	CUBIC FEET	SQ. FEET				
SKF2	27"	28 ½"	6.0	8.8	2	½ hp	3.9	210 LBS.
10345-01	21"	28 ½"	7.5	6.1	1	N/A	N/A	55 LBS.



Specifications subject to change without notice.

